

A-C® 5135

A-C® 5135 is an ethylene acrylic acid copolymer with high acid number and is supplied as a prill. It is used in coatings and adhesives to increase the adhesion and tack of the final formulated product. In plastic applications it is used to increase flow and lubricity. It is also used to help dispersion of pigments, fibers, flame retardants and other additives into plastics.

TYPICAL PROPERTIES

Property	Value
Hardness	7
Viscosity @ 140° C	1100
Drop Point, Mettler	92°C
Acid Number	135

REGULATORY APPROVALS

Property	Value
Plastic Pipe Institute/NSF*	No
FDA Indirect Approvals*	Yes

PRODUCT FORM AND SIZE

Property	Value
Product Form	Prill

DISCLAIMER: Although all statements and information contained herein are believed to be accurate and reliable, they are presented without guarantee or warranty of any kind, express or implied. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liability for use of the information and results obtained. Statements or suggestions concerning the use of materials and processes are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data and safety measures are indicated herein or that other measures may not be required.

© 2019 Honeywell International Inc.

All rights reserved

Honeywell