

A-C[®] 1973

High performance dispersing aid designed to improve pigment, additive and filler dispersion in master-batch applications. It can be used as the sole carrier or as part of a formulation where its ability to wet out, break down agglomerates and distribute pigment, additive and filler within the polymeric matrix enables higher loadings as well as the use of hard to disperse, untreated materials. Superior dispersion performance may allow for reduced manufacturing times and enhanced product characteristics.

TYPICAL PROPERTIES

Property	Value
Viscosity @ 140° C	375 cps
Drop Point, Mettler	104°C (219°F)
Acid Number	5 mg KOH/g

PRODUCT FORM AND SIZE

Property	Value
Product Form	Powder

REGULATORY APPROVALS

Property	Value
Plastic Pipe Institute/NSF*	No
FDA Indirect Approvals*	No

DISCLAIMER: Although all statements and information contained herein are believed to be accurate and reliable, they are presented without guarantee or warranty of any kind, express or implied. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liability for use of the information and results obtained. Statements or suggestions concerning the use of materials and processes are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data and safety measures are indicated herein or that other measures may not be required.

© 2018 Honeywell International Inc.

All rights reserved

Honeywell