

A-C[®] 5150

A-C[®] 5150 is an ethylene acrylic acid copolymer with high acid number, relatively low hardness and is supplied as a non-tacky solid. It is used in coatings and adhesives to increase the adhesion and tack of the final formulated product. In plastic applications it is used to increase flow and lubricity. It is also used to help dispersion of pigments, fibers, flame retardants and other additives into plastics.

TYPICAL PROPERTIES

Property	Value
Hardness	10
Viscosity @ 140° C	1000
Drop Point, Mettler	90°C
Acid Number	150

PRODUCT FORM AND SIZE

Property	Value
Product Form	Non-tacky solid

REGULATORY APPROVALS

Property	Value
Plastic Pipe Institute/NSF*	No
FDA Indirect Approvals*	Yes

DISCLAIMER: Although all statements and information contained herein are believed to be accurate and reliable, they are presented without guarantee or warranty of any kind, express or implied. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liability for use of the information and results obtained. Statements or suggestions concerning the use of materials and processes are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data and safety measures are indicated herein or that other measures may not be required.

© 2018 Honeywell International Inc.

All rights reserved

Honeywell